

Serial No.: 10/537,708
Examiner: Bach T. Dinh
Reply to Office Action Mailed December 23, 3008
Page2 of 10

RECEIVED
CENTRAL FAX CENTER

MAY 22 2009

Amendments to the Claims:

This listing of claims will replace all prior versions, and listing, of claims in the application.

1. (Currently amended) An analytical tool to be mounted to an analytical apparatus which includes a plurality of terminals and an analysis circuit, the analytical tool including comprising:

a substrate including a first end edge and a second end edge opposite to the first end edge;

a plurality of electrodes formed on the substrate for coming into contact with the plurality of terminals when mounted to the analytical apparatus, each of the electrodes extending along the substrate between the first end edge and the second end edge; and

a reagent portion formed on the substrate adjacent the first end edge of the substrate;

wherein[,] at least one of the electrodes serves as a disturbing-noise countermeasure electrode to which disturbing noise is more likely to come in comparison with the other electrodes other than said at least one of the electrodes, another of the electrodes serving as a working electrode; and

wherein the disturbing-noise countermeasure electrode extends toward the second end edge of the substrate and terminates at a first exposed end, the working electrode also extends toward the second end edge of the substrate and terminates at a second exposed end, the first exposed end of the disturbing-noise countermeasure electrode being located closer to the second end edge of the substrate than the second exposed end of the working electrode is to the second end edge of the substrate.

2. (Currently amended) The analytical tool according to claim 1, wherein the plurality of electrodes include a first electrode serving as the working electrode to be connected to the analysis circuit and a second electrode for applying voltage to a target portion in cooperation with the first electrode, and

Serial No.: 10/537,708
Examiner: Bach T. Dinh
Reply to Office Action Mailed December 23, 3008
Page3 of 10

wherein the second electrode serves as the disturbing-noise countermeasure electrode.

3. (Original) The analytical tool according to claim 2, wherein the second electrode is not electrically connected to the analysis circuit when the analytical tool is mounted to the analytical apparatus.

4. (Original) The analytical tool according to claim 3, wherein the plurality of terminals of the analytical apparatus include a ground connection terminal connected to ground, and

wherein the second electrode comes into contact with the ground connection terminal when the analytical tool is mounted to the analytical apparatus.

5. (Currently amended) The analytical tool according to claim 1, wherein the plurality of electrodes include a first electrode serving as the working electrode to be connected to the analysis circuit, a second electrode for applying voltage to a target portion in cooperation with the first electrode, and a third electrode which is not involved in the voltage application to the target portion, and

wherein the third electrode serves as the disturbing-noise countermeasure electrode.

6. (Original) The analytical tool according to claim 5, wherein the third electrode is not electrically connected to the analysis circuit when the analytical tool is mounted to the analytical apparatus.

7. (Original) The analytical tool according to claim 6, wherein the plurality of terminals of the analytical apparatus include a ground connection terminal connected to ground, and

wherein the third electrode comes into contact with the ground connection terminal when the analytical tool is mounted to the analytical apparatus.

Serial No.: 10/537,708
Examiner: Bach T. Dinh
Reply to Office Action Mailed December 23, 3008
Page4 of 10

8. (Currently amended) The analytical tool according to claim 1, wherein the plurality of electrodes include a first electrode serving as the working electrode to be connected to the analysis circuit, a second electrode for applying voltage to a target portion in cooperation with the first electrode, and a third electrode which is not involved in the voltage application to the target portion, and

wherein each of the second and ~~[[the]]~~ third electrodes serves ~~serve~~ as the disturbing-noise countermeasure electrode.

9. (Original) The analytical tool according to claim 8, wherein the third electrode is not electrically connected to the analysis circuit when the analytical tool is mounted to the analytical apparatus.

10. (Original) The analytical tool according to claim 9, wherein the plurality of terminals of the analytical apparatus include a ground connection terminal connected to ground, and

wherein the third electrode comes into contact with the ground connection terminal when the analytical tool is mounted to the analytical apparatus.

11. (Original) The analytical tool according to claim 1, further comprising a flow path for moving a sample, and an air vent for discharging air from the flow path.

12. (Original) The analytical tool according to claim 11, wherein the disturbing-noise countermeasure electrode includes an input portion to which disturbing noise coming through the air vent is inputted.

13. (Original) The analytical tool according to claim 12, wherein the input portion is at least partially exposed via the air vent.

Serial No.: 10/537,708
Examiner: Bach T. Dinh
Reply to Office Action Mailed December 23, 3008
Page 5 of 10

14. (Original) The analytical tool according to claim 13, wherein the input portion is provided directly below the air vent and partially covered by an insulating film, and wherein the insulating film includes an opening for partially exposing the input portion.
15. (Currently amended) The analytical tool according to claim 12, further comprising ~~a substrate on which the plurality of electrodes are formed, and~~ a cover which is bonded to the substrate and in which the air vent is formed, wherein, ~~in plan view,~~ the input portion includes a part located at a periphery of the air vent.
16. (Currently amended) The analytical tool according to claim 15, wherein, ~~in plan view,~~ the input portion surrounds the air vent.
17. (Original) The analytical tool according to claim 1, wherein the disturbing-noise countermeasure electrode surrounds at least one of the plurality of electrodes except the disturbing-noise countermeasure electrode.
18. (Currently amended) The analytical tool according to claim 1, ~~further comprising a substrate on which the plurality of electrodes are formed,~~ wherein the disturbing-noise countermeasure electrode is formed along a periphery of the substrate.
19. (Original) The analytical tool according to claim 1, wherein when the analytical tool is mounted to the analytical apparatus, the disturbing-noise countermeasure electrode comes into contact with a corresponding one of the terminals of the analytical apparatus earlier in comparison with the other electrodes than the disturbing-noise countermeasure electrode.
20. (Canceled)

Serial No.: 10/537,708
Examiner: Bach T. Dinh
Reply to Office Action Mailed December 23, 3008
Page 6 of 10

21. (Original) The analytical tool according to claim 1, further comprising a pinch portion which is utilized in mounting the analytical tool to the analytical apparatus or detaching the analytical tool from the analytical apparatus.
22. (Currently amended) The analytical tool according to claim 21, wherein the disturbing-noise countermeasure electrode is covered by an insulating film ~~except~~ except for an exposed portion adjacent to the pinch portion.
23. (Currently amended) The analytical tool according to claim 22, wherein the pinch portion comprises a recess formed at a side edge ~~which is inwardly sunk in a plan view of~~ the analytical tool.
24. (New) A combination of an analytical tool and an analytical apparatus, the analytical tool being mounted on the analytical apparatus for analysis;
the analytical apparatus comprising a plurality of terminals and an analysis circuit, the plurality of terminals including a voltage applying terminal and a grounding terminal;
the analytical tool comprising a plurality of electrodes including a working electrode and a grounding electrode serving as a disturbing-noise countermeasure electrode; and
wherein when the analytical tool is mounted to the analytical apparatus, the disturbing-noise countermeasure electrode comes into contact with the grounding terminal of the analytical apparatus earlier than the working electrode comes into contact with the voltage applying terminal.